Safety Data Sheet PRIMER MF comp. A

Safety Data Sheet dated: 07/02/2023 - version 5



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: PRIMER MF comp. A

Trade code: 902411 UFI: 0C90-30RT-100Q-S9J8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Epoxy resins

Uses advised against: Data not available.

1.3. Details of the supplier of the safety data sheet

Company: MAPEI S.p.A. - Via Cafiero, 22 - 20158 Milano

Tel. +(39)02376731 (office hours) - Fax: +39-02-37673.214 - www.mapei.it

Responsable: sicurezza@mapei.it

1.4. Emergency telephone number

Centro antiveleni, Azienda ospedaliera "Antonio Cardarelli", III Servizio di anestesia e rianimazione, via Antonio Cardarelli 9, Napoli - Tel. 081 5453333

Centro antiveleni, Azienda ospedaliera universitaria Careggi, U.O. Tossicologia medica, via Largo Brambilla 3, Firenze - Tel. 055 7947819 Centro antiveleni, Centro nazionale d'informazione tossicologica, IRCCS Fondazione Salvatore Maugeri Clinica del lavoro e della riabilitazione, via Salvatore Maugeri 10, Pavia - Tel. 0382 24444

Centro antiveleni, Azienda ospedaliera Niguarda Ca' Granda, piazza Ospedale Maggiore 3, Milano - Tel. 02 66101029

Centro antiveleni, Azienda ospedaliera "Papa Giovanni XXIII", Tossicologia clinica, Dipartimento di farmacia clinica e farmacologia, piazza OMS 1, Bergamo - Tel. 800 883300

Centro antiveleni Policlinico "Umberto I", PRGM tossicologia d'urgenza, viale del Policlinico 155, Roma - Tel. 06 49978000

Centro antiveleni del Policlinico "Agostino Gemelli", Servizio di tossicologia clinica, largo Agostino Gemelli 8, Roma - Tel. 06 3054343

Centro antiveleni, Azienda ospedaliera universitaria Riuniti, viale Luigi Pinto 1, Foggia - Tel. 800 183459

Centro antiveleni, Ospedale pediatrico Bambino Gesù, Dipartimento emergenza e accettazione DEA, piazza Sant'Onofrio 4, Roma - Tel. 06 68593726

Centro antiveleni dell'Azienda ospedaliera universitaria integrata (AOUI) di Verona sede di Borgo Trento, piazzale Aristide Stefani, 1 - 37126 Verona - Tel. 800 011858

SECTION 2: Hazards identification





2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

Skin Sens. 1A May cause an allergic skin reaction.

Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words



Warning

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Print date 09/02/2023 Production Name PRIMER MF comp. A Page n. 1 of 10

Precautionary statements

P261 Avoid breathing mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage.

Special Provisions:

EUH208 Contains bis-[4-(2,3-epoxipropoxi)phenyl]propane. May produce an allergic reaction.

EUH208 Contains oxirane, mono[(C12-14-alkyloxy)methyl] derivs.. May produce an allergic reaction.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Contains

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: No other hazards

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

This preparation contains low molecular weight epoxy resins. Cross sensitisation to other epoxies is possible. Avoid also exposure to spray mist and vapour.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not Relevant

3.2. Mixtures

Mixture identification: PRIMER MF comp. A

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥50 - <75 %	bis-[4-(2,3- epoxipropoxi)phenyl]propane	CAS:1675-54-3, 25085-99-8 EC:216-823-5 Index:603-073-	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411	01-2119456619-26
		00-2	Specific Concentration Limits: C ≥ 5%: Skin Irrit. 2 H315 C ≥ 5%: Eye Irrit. 2 H319	
≥20 - <25 %	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.		Skin Irrit. 2, H315; Skin Sens. 1B, H317	01-2119485289-22-XXXX
≥10 - <20 %	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	CAS:9003-36-5 EC:701-263-0	Skin Irrit. 2, H315; Aquatic Chronic 2, H411; Skin Sens. 1, H317	01-2119454392-40-XXXX
≥10 - <20 %	bis(isopropyl)naphthalene	CAS:38640-62-9 EC:254-052-6	Asp. Tox. 1, H304; Aquatic Chronic 1, H410	01-2119565150-48-XXXX

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately

Print date 09/02/2023 Production Name PRIMER MF comp. A Page n. 2 of 10

with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Print date 09/02/2023 Production Name PRIMER MF comp. A Page n. 3 of 10

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Predicted No Effect Concentration (PNEC) values

alkyloxy)methyl] derivs.

oxirane, mono[(C12-14- Exposure Route: Marine water; PNEC Limit: 0,00072 mg/l

CAS: 68609-97-2

Exposure Route: Fresh Water; PNEC Limit: 0,0072 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 66,77 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 6,677 mg/kg

Exposure Route: Soil; PNEC Limit: 80,12 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l Formaldehyde, oligomeric Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

reaction products with 1chloro-2,3-epoxypropane

and phenol CAS: 9003-36-5

Exposure Route: Fresh Water; PNEC Limit: 0,003 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0,294 mg/kg

Exposure Route: Marine water; PNEC Limit: 0,0003 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 0,0294 mg/kg

Exposure Route: Soil; PNEC Limit: 0,237 mg/kg

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards. like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

In case of insufficient ventilation use mask with ABEKP filters (EN 14387).

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Appearance: liquid Color: transparent Odour: Characteristic

Odour threshold: Not available

Melting point / freezing point: Not available Initial boiling point and boiling range: Not available

Print date 09/02/2023 Production Name PRIMER MF comp. A Page n. 4 of Flammability: N.A.

Upper/lower flammability or explosive limits: Not available

Flash point: Not available

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: Not available Viscosity: 350.00 cPs

Kinematic viscosity: Not available Solubility in water: Insoluble Solubility in oil: soluble

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available Relative density: 1.17 g/cm3 Vapour density: Not available **Particle characteristics:** Particle size: Not available

9.2. Other information

Miscibility: Not available Conductivity: Not available Explosive properties: == No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological Information of the Preparation

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation The product is classified: Skin Irrit. 2(H315) c) serious eye damage/irritation The product is classified: Eye Irrit. 2(H319) d) respiratory or skin sensitisation The product is classified: Skin Sens. 1A(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

bis-[4-(2,3- a) acute toxicity LD50 Skin Rabbit = 20 mg/kg

Print date 09/02/2023 Production Name PRIMER MF comp. A Page n. 5 of 10

LD50 Oral Rat = $11300 \mu L/kg$ LD50 Skin Rabbit = 20000 mg/kg

oxirane, mono[(C12-14- a) acute toxicity

alkyloxy)methyl] derivs.

LD50 Oral Rat = 19200 mg/kg

LD50 Skin Rabbit = 4000, mg/kg

Formaldehyde, oligomeric a) acute toxicity

reaction products with 1chloro-2,3-epoxypropane and phenol

LD50 Skin Rat > 2000 mg/kg

LD50 Oral Rat > 5000, mg/kg

i) STOT-repeated

exposure

NOAEL Oral = 250 mg/kg

bis(isopropyl)naphthalene a) acute toxicity

LD50 Oral Rat > 4000 mg/kg LD50 Skin Rat > 4000 mg/kg LC50 Inhalation Rat > 5,6 mg/l 4h LD50 Skin Rat > 4500 mg/kg LC50 Inhalation Rat > 5,64 mg/l 4h LD50 Oral Rat = 3900 mg/kg

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 2(H411)

List of Eco-Toxicological properties of the components

List of Eco-Toxicological properties of the components					
	Component	Ident. Numb.	Ecotox Data		
	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS: 68609-97- 2 - EINECS: 271-846-8 - INDEX: 603- 103-00-4	a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96h		
			a) Aquatic acute toxicity: EL50 Daphnia = 7,2 mg/L 48h		
			a) Aquatic acute toxicity: EC50 Algae = 843 mg/L 72h		
			b) Aquatic chronic toxicity: NOEC Algae = 500 mg/L 72h		
	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	CAS: 9003-36-5 - EINECS: 701- 263-0	a) Aquatic acute toxicity: LC50 Fish = 5,7 mg/L 96h		
			a) Aquatic acute toxicity: EC50 Daphnia = 2,55 mg/L 48h		
			a) Aquatic acute toxicity: EC50 Algae = 1,8 mg/L 72h		
	bis(isopropyl)naphthalene	CAS: 38640-62- 9 - EINECS: 254-052-6	a) Aquatic acute toxicity: LL50 Daphnia = 1,7 mg/L 48		
			a) Aquatic acute toxicity: NOEC Daphnia = 0,013 mg/L -		

Print date 09/02/2023 **Production Name** PRIMER MF comp. A Page n. 6 of 10

21 d

a) Aquatic acute toxicity: LC50 Fish Cyprinus carpio > 1000 mg/L 96h a) Aquatic acute toxicity: LC50 Fish Oryzias latipes > 1000 mg/L 96h

12.2. Persistence and degradability

Component Persitence/Degradability:

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Readily biodegradable

12.3. Bioaccumulative potential

Component

Bioaccumulation

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Not bioaccumulative

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

14.1. UN number or ID number

3082

14.2. UN proper shipping name

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins) IATA-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins) IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins)

14.3. Transport hazard class(es)

ADR-Class: 9
IATA-Class: 9
IMDG-Class: 9

14.4. Packing group

ADR-Packing Group: III IATA-Packing group: III IMDG-Packing group: III

14.5. Environmental hazards

Print date 09/02/2023 Production Name PRIMER MF comp. A Page n. 7 of 10

Marine pollutant: Yes Environmental Pollutant: Yes IMDG-EMS: F-A, S-F

14.6. Special precautions for user

Road and Rail (ADR-RID): ADR exempt: No ADR-Label: 9

> ADR-Hazard identification number: 90 ADR-Special Provisions: 274 335 375 601

ADR-Transport category (Tunnel restriction code): 3 (-)

Air (IATA):

IATA-Passenger Aircraft: 964 IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisions: A97 A158 A197

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 274 335 969

IMDG-EMS: F-A, S-F

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

These substances, when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids, or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to provisions of ADR, IMDG and IATA DGR.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): 45 (A+B) g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (LO) II. 2017/770 (ATF TO CLF)

Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP)

negalation (EU) in 2019/321 (/// 12 CE)

Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EO) II. 2020/1102 (ATI 15 CE)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)
Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according Lower-tier threshold (tonnes) Upper-tier threshold (tonnes) to Annex 1, part 1

Product belongs to category: E2 200 500

Print date 09/02/2023 Production Name PRIMER MF comp. A Page n. 8 of 10

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 75

SVHC Substances:

SVHC substances not present in a concentration $\geq 0.1\%$ (w/w)

National regulations

Lagerklasse (TRGS-510): 12 - Non-combustible liquids, that cannot be assigned to any of the aforementioned LGK

German Water Hazard Class.

Class 3: extremely hazardous.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description		
H304	May be fatal if swallowed and enters airways.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
Code	Hazard class and hazard category	Description	
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1	
3.2/2	Skin Irrit. 2	Skin irritation, Category 2	
3.3/2	Eye Irrit. 2	Eye irritation, Category 2	
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1	
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A	
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B	
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1	
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
3.2/2	Calculation method
3.3/2	Calculation method
3.4.2/1A	Calculation method
4.1/C2	Calculation method

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures) BCF: Biological Concentration Factor BEI: Biological Exposure Index

Print date 09/02/2023 Production Name PRIMER MF comp. A Page n. 9 of 10

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand COV: Volatile Organic Compound CSA: Chemical Safety Assessment CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive DSD: Dangerous Substances Directive EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification

- SECTION 3: Composition/information on ingredients

- SECTION 8: Exposure controls/personal protection

- SECTION 9: Physical and chemical properties

- SECTION 11: Toxicological information

- SECTION 12: Ecological information

- SECTION 15: Regulatory information

- SECTION 16: Other information

Print date 09/02/2023 Production Name PRIMER MF comp. A Page n. 10of 10